MICHELMAN

Michem® Emulsion 94340

| BRAND FAMILY OVERVIEW | Michem® Emulsion is a versatile family of products that adds value to a wide range of markets. These markets include paint & coatings, fiberglass, inks & OPVs, floor care, wood finishes, automotive care products, building products, carpets, die lubricants, textiles and urethane foam. | | |
|------------------------|---|--|--|
| USAGE | A phenol-free additive is best used in floor polish and overprint varnish formulations when a high degree of slip resistance is needed. It also provides durability and scratch resistance to wood applications. | | |
| DESCRIPTION | Polypropylene emulsion | | |
| PERFORMANCE ATTRIBUTES | This product is used in many applications including the following: | | |
| | Market | Properties Imparted | |
| | Building Paints | abrasion resistance, block resistance, mold release, scratch resistance, slip resistance | |
| | Cable & Cordage | fiber treatment | |
| | Die Lubes & Mold Releases | abrasion resistance, block resistance, mold release, scratch resistance, slip resistance | |
| | Exterior Wood Protection | abrasion resistance, block resistance, durability, mold release, scratch resistance, slip resistance | |
| | Gloves | abrasion resistance, block resistance | |
| | Industrial & Institutional | abrasion resistance, block resistance, durability, mold release, scratch resistance, slip resistance | |
| | Inks | abrasion resistance, block resistance, mold release, scratch resistance, slip resistance | |
| | Interior Furniture & Floor | abrasion resistance, block resistance, mold release, scratch resistance, slip resistance | |
| | Metalworking Fluids | release | |
| | OEM Applied Wood Protection | abrasion resistance, block resistance, mold release, scratch resistance, slip resistance | |
| | Overprint Varnishes | abrasion resistance, block resistance, durability, mold release, scratch resistance, slip resistance | |

MICHELMAN

Michem® Emulsion 94340

| IES The fo | The following properties are typical but should not be considered specifications: | | |
|---------------|--|-----------------------------|--|
| Арр | earance: | Amber, translucent liquid | |
| Solic | ds Type: | Polypropylene | |
| Free | ze/Thaw Stability: | None: protect from freezing | |
| Non | -Volatile (%) : | 39.5 - 40.5 | |
| Spea | cific Gravity: | 0.99 - 1.01 | |
| pH: | | 7.5 - 9.0 | |
| Reco | ommended pH of your syst | em: > 7.0 | |
| Broc | kfield Viscosity (cps) : | 120 max | |
| S | pindle Number: | 2 | |
| R | PM: | 60 | |
| DE) | | | |
| | Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing. Keep out of the reach of children. Store locked up. | | |
| cloth vent | Avoid contact with eyes, skin and clothing. Avoid contact with skin, eyes or clothing. Do not eat, drink or smoke when using this product. Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required. | | |
| Use | | • | |

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

MICHELMAN

Michem® Emulsion 94340

Americas

Michelman Inc. Tel: +1 513 793 7766 Fax: +1 513 793 2504

China

Michelman New Material (Shanghai) Co., Ltd. Tel: +86 21 3810 3800 Fax: +86 21 3810 3811

Luxembourg

India

Michelman International SARL Tel: +352 26 39 44 1 Fax: +352 26 39 44 80

Michelman Private Limited

Fax: +91 22 6221 3801/02

Tel: +91 22 6221 3800

Michal

Singapore

Michelman Asia-Pacific Pte. Ltd. Tel: +65 6861 2822 Fax: +65 6861 2262

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2025 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified.