MICHELMAN

Michem® Emulsion 67235

BRAND FAMILY OVERVIEW	Michem [®] Emulsion is a versatile family of products that adds value to a wide range of markets. These markets include paint & coatings, fiberglass, inks & OPVs, floor care, wood finishes, automotive care products, building products, carpets, die lubricants, textiles and urethane foam.			
USAGE	A phenol free additive best used in water based coatings where improved slip, rub resistance, hardness and/or block resistance is needed. It has proven very effective for mar resistance in floor polish formulations, as well as mar resistance and shine in car polish formulations.			
DESCRIPTION	High density polyethylene emulsion			
PERFORMANCE ATTRIBUTES	This product is used in many applications including the following:			
	Market	Properties Imparted		
	Automotive Care	APEO free, mar resistance		
	Gloves	block resistance		
	Industrial & Institutional	abrasion resistance, block resistance, hardness, mar resistance, rub resistance		
	Inks	lubricity, mar resistance, rub resistance, scratch resistance		
	OEM Applied Wood Protection	abrasion resistance, block resistance, lubricity, scratch resistance		
	Overprint Varnishes	block resistance, gloss enhancement, rub resistance, scratch resistance		
PHYSICAL PROPERTIES	The following properties are typical but should not be considered specifications:			
	Appearance:	Translucent liquid		
	Solids Type:	High Density Polyethylene		
	Freeze/Thaw Stability:	None: protect from freezing		
	Non-Volatile (%) :	34.0 - 36.0		
	Specific Gravity:	0.99 - 1.01		
	pH:	9.7 - 11.0		
	Recommended pH of your system:	> 7.0		
	Brookfield Viscosity (cps) :	< 50		
	Spindle Number:	1		
	RPM:	60		

MICHELMAN

Michem® Emulsion 67235

SITE OF MANUFACTURE (and PRODUCT CODE)	USA (ME67235)			
STORAGE	Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.			
HANDLING	Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required.			
	Revised 24 January 2025 The following information for this product, specific to each site of manufacture, is available upon request: • Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing) • Food Contact Declaration of Compliance (if applicable)			
	Americas	Luxembourg	Singapore	
	Michelman Inc. Tel: +1 513 793 7766 Fax: +1 513 793 2504	Michelman International SARL Tel: +352 26 39 44 1 Fax: +352 26 39 44 80	Michelman Asia-Pacific Pte. Ltd. Tel: +65 6861 2822 Fax: +65 6861 2262	
	China	India		
	Michelman New Material (Shanghai) Co., Ltd. Tel: +86 21 3810 3800 Fax: +86 21 3810 3811	Michelman Private Limited Tel: +91 22 6221 3800 Fax: +91 22 6221 3801/02		

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2025 MICHELMAN, INC. All rights reserved. [®] Reg. U.S. Pat. TM Off. All marks contained herein are registered or owned by Michelman, Inc. Michelman is ISO 9001:2015 certified.