

# Michem® In-Line Primer Q4324A

---

**BRAND FAMILY OVERVIEW** Primers explicitly designed for use on HP Indigo equipment with an in-line priming applicator to impart a print-receptive surface to most substrates, and improve the ink transfer and adhesion of HP Indigo ElectroInk.

**USAGE** Designed as a primer for HP Indigo substrates to render them compatible to ink. It can be used on coated paper substrates on the in-line priming unit on the 6K and W7200 presses.

**DESCRIPTION** Print receptive primer

**PHYSICAL PROPERTIES** The following properties are typical but should not be considered specifications:

Appearance:	Translucent liquid
pH:	10.4 - 11.4
Shelf Life (months) :	The product has a shelf life of 24 months from date of manufacture when storage and handling instructions are followed.

**SITE OF MANUFACTURE (and PRODUCT CODE)** USA (Q4324A), Belgium (Q4324A.E), Singapore (Q4324A.S)

**APPLICATION DATA** Michem® In-Line Primer Q4324A can be applied using the in-line priming unit of the HP Indigo 6K and W7200 printing presses. When run as instructed by HP Indigo on coated paper substrates, the ILP unit will apply the correct amount of primer to achieve optimal ink adhesion and press performance. For certain coated paper label applications, Michem® In-Line Primer Q4324A is another certified option that can be run interchangeably with DP680. ISO Cup Viscosity - #3 Cup 21-27 sec. Do not dilute.

**STORAGE** Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

**HANDLING** Avoid contact with eyes, skin and clothing. Ensure adequate ventilation. Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required.

# Michem® In-Line Primer Q4324A

---

Revised 16 March 2023

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

---

## Americas

Michelman Inc.  
Tel: +1 513 793 7766  
Fax: +1 513 793 2504

## Luxembourg

Michelman International SARL  
Tel: +352 26 39 44 1  
Fax: +352 26 39 44 80

## Singapore

Michelman Asia-Pacific Pte. Ltd.  
Tel: +65 6861 2822  
Fax: +65 6861 2262

## China

Michelman New Material  
(Shanghai) Co., Ltd.  
Tel: +86 21 3810 3800  
Fax: +86 21 3810 3811

## India

Michelman Private Limited  
Tel: +91 22 6221 3800  
Fax: +91 22 6221 3801/02

---

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2025 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.

All marks contained herein are registered or owned by Michelman, Inc.

Michelman is ISO 9001:2015 certified.