

NatureShield® 60

BRAND FAMILY OVERVIEW NatureShield® additives for wood & concrete surface coatings are designed to improve the durability, weatherability, and aesthetics of wood and stone-based substrates. These environmentally-friendly additives impart abrasion, scratch, & water resistance, provide good water beading, and enhance the natural pattern of wood. Comprised of naturally-derived materials, many NatureShield® products are certified under the USDA BioPreferred Program.

USAGE This additive provides scratch and abrasion resistance to various building paints, and OEM & on-site applied wood protection and concrete applications.

DESCRIPTION Proprietary wax emulsion

PERFORMANCE ATTRIBUTES This product is used in many applications including the following:

Market	Properties Imparted
Automotive Care	<i>abrasion resistance, mar resistance, scratch resistance</i>
Concrete	<i>abrasion resistance, scratch resistance</i>
OEM Applied Wood Protection	<i>abrasion resistance, scratch resistance</i>
On-Site Applied Wood Protection	<i>abrasion resistance, scratch resistance</i>

PHYSICAL PROPERTIES The following properties are typical but should not be considered specifications:

Appearance:	Whitish liquid
Solids Type:	Proprietary
Emulsifier Charge:	Nonionic
Non-Volatile (%) :	29.5 - 30.5
pH:	3.5 - 6.0
Brookfield Viscosity (cps) :	0 - 100
Spindle Number:	1
RPM:	60

STORAGE Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

HANDLING Avoid contact with eyes. Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required.

NatureShield® 60

Revised 08 August 2023

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc.
Tel: +1 513 793 7766
Fax: +1 513 793 2504

Luxembourg

Michelman International SARL
Tel: +352 26 39 44 1
Fax: +352 26 39 44 80

Singapore

Michelman Asia-Pacific Pte. Ltd.
Tel: +65 6861 2822
Fax: +65 6861 2262

China

Michelman New Material
(Shanghai) Co., Ltd.
Tel: +86 21 3810 3800
Fax: +86 21 3810 3811

India

Michelman Private Limited
Tel: +91 22 6221 3800
Fax: +91 22 6221 3801/02

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2024 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.

All marks contained herein are registered or owned by Michelman, Inc.

Michelman is ISO 9001:2015 certified.