

Release Coat® 40

BRAND FAMILY OVERVIEW Single-component Release Coat® keeps hot rubber and asphalt from sticking to corrugated containers without the use of a costly plastic bag. It is easy to use, requires no mixing, is corrugator-applied and repulpable.

USAGE An easy-to-use one component silicone emulsion coating that provides superior release for a variety of "sticky" products such as hot asphalt. Because it is a one component release system, it eliminates mixing and leftover material disposal. This product is neither hot melt nor cold set gluable.

DESCRIPTION One component, water based release coating.

PERFORMANCE ATTRIBUTES This product is used in many applications including the following:

| Market | Properties Imparted |
|------------|---------------------|
| Industrial | release |

PHYSICAL PROPERTIES The following properties are typical but should not be considered specifications:

| | |
|------------------------------|----------------------|
| Appearance: | White, opaque liquid |
| Solids Type: | Silicone |
| pH: | 10.4 - 11.4 |
| Brookfield Viscosity (cps) : | 200 - 625 |
| Spindle Number: | 3 |
| RPM: | 60 |

SITE OF MANUFACTURE (and PRODUCT CODE) USA (RLC40), Singapore (RLC40.S)

APPLICATION DATA Release Coat® 40 may be blade or rod applied at the wet or dry end of the corrugator.

STORAGE Keep container tightly closed. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep from freezing.

HANDLING Avoid contact with eyes, skin and clothing. Handle in accordance with good industrial hygiene and safety practice. Use personal protective equipment as required.

Release Coat® 40

Revised 12 May 2017

The following information for this product, specific to each site of manufacture, is available upon request:

- Material Safety Data Sheets in various formats and languages (includes global chemical inventory listing)
- Food Contact Declaration of Compliance (if applicable)

Americas

Michelman Inc.
Tel: +1 513 793 7766
Fax: +1 513 793 2504

Luxembourg

Michelman International SARL
Tel: +352 26 39 44 1
Fax: +352 26 39 44 80

Singapore

Michelman Asia-Pacific Pte. Ltd.
Tel: +65 6861 2822
Fax: +65 6861 2262

China

Michelman New Material
(Shanghai) Co., Ltd.
Tel: +86 21 3810 3800
Fax: +86 21 3810 3811

India

Michelman Private Limited
Tel: +91 22 6221 3800
Fax: +91 22 6221 3801/02

The facts stated and the recommendations contained herein are based on our own research and the research of others, and are believed to be accurate. However, no guarantee of their accuracy is made because we cannot cover every possible application for our products nor anticipate every variation encountered in manufacturing equipment and methods. The products discussed are sold without warranty, express or implied and Seller disclaims any warranty of merchantability or fitness for a particular purpose in connection with the purchase of its products. It is recommended that purchasers conduct their own tests to determine the suitability of such products for their particular purpose. Seller shall not be liable for any injury, loss or damage, direct or consequential arising out of the use of or the inability to use the product. Statements concerning the possible use of our products are not intended as recommendations to use our products in the infringement of any patent and our products are sold without warranty of non-infringement.

© 2025 MICHELMAN, INC. All rights reserved. ® Reg. U.S. Pat. TM Off.

All marks contained herein are registered or owned by Michelman, Inc.

Michelman is ISO 9001:2015 certified.